short gas-chex[®] FOR ETHYLENE OXIDE (EO) STERILIZATION

Reorder No.: 26900100

INSTRUCTION FOR USE

The Gas-Chex Indicator is an integrating indicator designed to respond to all critical parameters over a specified range of Ethylene Oxide sterilization cycles. The Gas-Chex Indicator is intended to be placed in each pack, pouch, tray or other containment device to function as an independent monitor of critical parameters for the following sterilization cycles:

TEMPERATURE	ETHYLENE OXIDE	RH%	EXPOSURE TIME
37°C	736 mg/L	≥35%	3 hours
37°C	759 mg/L	≥35%	3 hours
38°C	736 mg/L	40-80%	4.5 hours
38°C	759 mg/L	40-80%	4.5 hours
55°C	736 mg/L	≥35%	1 hour
55°C	759 mg/L	≥35%	1 hour
55°C	600 mg/L	60%	4 hours

The Gas-Chex Indicator for EO sterilization has the following minimum Stated Values determined in a Resistometer:

54°C, 42 min, EO 600 mg/L, RH 60±10% 37°C, 75 min, EO 600 mg/L, RH 60±10%

55°C, 36 min, EO 736 mg/L, RH 50±10% 37°C, 75 min, EO 736 mg/L, RH 50±10%

55°C, 35 min, EO 759 mg/L, RH 50±10% 37°C, 75 min, EO 759 mg/L, RH 50±10%

gas-chex

THE RED WORD gas-chex® CHANGES TO GREEN WHEN EO PROCESSED PROPPER REORDER NO. 26900100

gas-chex THE RED WORD gas-chex® CHANGES TO GREEN WHEN EO PROCESSED PROPPER REORDER NO. 26900100

HOW TO USE gas-chex[®] STERILIZATION INDICATOR STRIPS AND INTERPRET THE RESULTS:

Place a Gas-Chex strip into each pack. After processing, when sterile presentation is made, examine the Gas-Chex mark; it must be green. Brown color or the original red unchanged indicates underprocessing, do not use the contents of the pack. Return for reprocessing and determine the cause of the failure.

Unprocessed Gas-Chex strip should be stored between $15^{\circ}C/59^{\circ}F-30^{\circ}C/86^{\circ}F$ and <60% relative humidity. When stored as indicated, this product has 36 months shelf life from the date of manufacture. For record keeping purposes, use the same storage conditions and protect from light.

REMEMBER YOUR SIGNAL OF SAFETY IS GREEN



36-04 Skillman Avenue Long Island City, NY 11101 Tel. (718) 392-6650 • Fax. (718) 482-8909 www.proppermfg.com